

# PA-917 LS PRIMER



## Commercial Product Data Sheet

### **Product Description**

PA-917 LS Primer is an asphalt solvent blend designed as a primary coating for metal and masonry surfaces prior to application of Siplast Roofing and Flashing Systems.

### **Product Uses**

PA-917 LS Primer is applied to all metal flanges and concrete and masonry surfaces. The primer should be allowed to dry thoroughly prior to application of Siplast Roofing and Flashing Systems. PA-917 LS Primer can be applied by brush or spray. Do not dilute PA-917 LS Primer. Diluting PA-917 LS using petroleum solvents will affect its bonding and drying characteristics.

### **Product Approvals**

PA-917 LS meets or exceeds the requirements for ASTM D41 Type II for asphalt primer used in roofing.

PA-917 LS Primer meets current regional VOC regulations.

VOC content: This product contains max. 350 g/l VOC.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 8/2011

### **COMMERCIAL PRODUCT INFORMATION**

Unit: 5-Gallon Pail  
4.7 gallons (17.8 liters) net content

Coverage: Coverage is dependent on the condition of the surface receiving the primer. The coverage ranges from 100 square feet per gallon (0.4 liter per m<sup>2</sup>) on very rough, porous surfaces to 300 square feet per gallon (1.2 liter per m<sup>2</sup>) on smooth, low-absorptive surfaces.

Flash Point, Pensky-Martens Closed Cup: >105°F (41°C)

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 45 in X 48 in (114 cm X 122 cm) wooden pallet  
Number Pails Per Pallet: 42  
Number Pallets Per Truckload: 22  
Weight Per Pail: 40 lb (18.1 kg)  
Weight Per Drum: 507 lb (230 kg)

Shipping Classifications: White Label (combustible)

Storage and Handling: All containers of PA-917 LS Primer should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.