

# PA-1125 PRIMER



## Commercial Product Data Sheet

---

### **Product Description**

PA-1125 Primer is an asphalt solvent blend designed as a primary coating for metal and masonry surfaces prior to application of Siplast Roofing and Flashing Systems.

### **Product Uses**

PA-1125 Primer is applied to all metal flanges and concrete and masonry surfaces; the primer should be allowed to dry thoroughly prior to application of Siplast Roofing and Flashing Systems. PA-1125 Primer can be applied by brush or spray. Diluting PA-1125 using petroleum solvents will affect its bonding and drying characteristics.

### **Product Approvals**

PA-1125 meets or exceeds the requirements for Federal Specification SSA-701B and ASTM D 41 for asphalt primer used in roofing.

### **COMMERCIAL PRODUCT INFORMATION**

---

Unit: 5-Gallon Pail  
4.7 gallons (17.8 liters) net content

Coverage: Coverage is dependent on the condition of the surface receiving the primer. The coverage ranges from 100 square feet per gallon (0.4 liter per 1/m<sup>2</sup>) on very rough, porous surfaces to 400 square feet per gallon (1.6 1/m<sup>2</sup>) on smooth, low-absorptive surfaces.

Flash Point, Pensky-Martens Closed Cup: 100°F (38°C)

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 36 in X 48 in (91 cm X 122 cm) wooden pallet  
Number Pails Per Pallet: 36  
Number Pallets Per Truckload: 22  
Weight Per Pail: 37 lb (16.8 kg)

Shipping Classifications: White Label (combustible)

Storage and Handling: All containers of PA-1125 Primer should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 9/08