

PA-828 FLASHING CEMENT



Commercial Product Data Sheet

Product Description

PA-828 Flashing Cement is specially formulated for use as a roofing membrane base flashing cement. It is produced from refined asphalt and low aromatic petroleum solvents with non-asbestos fibers added for reinforcement and enhanced slump resistance compared with general-purpose plastic cement.

Product Uses

PA-828 Flashing Cement is designed for use with guaranteed Siplast Roof Systems as a membrane flashing adhesive. PA-828 is slump resistant and highly flexible for high slope and vertical applications. For best results with flashing applications, PA-828 should be applied using a notched trowel. PA-828 may also be used alternatively to PA-1021 as a mastic for setting all metal flanges and drain lead flashings.

Product Approvals

PA-828 Flashing Cement meets or exceeds the requirements of ASTM D 4586 Type II for asbestos free, asphalt based roof cement.

COMMERCIAL PRODUCT INFORMATION

Unit: 5-Gallon Pail
4.7 gallons (17.8 liters) net content

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 36 in X 48 in (91 cm X 122 cm) wooden pallet
Number Pails Per Pallet: 36
Number Pallets Per Truckload: 22
Weight Per Pail: 51 lb (23 kg)

Shipping Classification: White Label (combustible)

Storage and Handling: All containers of PA-828 Flashing Cement should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 10/07