

# PA-828 FLASHING CEMENT



## Commercial Product Data Sheet

---

### **Product Description**

PA-828 Flashing Cement is specially formulated for use as a roofing membrane base flashing cement. It is produced from refined asphalt and low aromatic petroleum solvents with non-asbestos fibers added for reinforcement and enhanced slump resistance compared with general-purpose plastic cement.

### **Product Uses**

PA-828 Flashing Cement is designed for use with guaranteed Siplast Roof Systems as a membrane flashing adhesive. PA-828 is slump resistant and highly flexible for high slope and vertical applications. For best results with flashing applications, PA-828 should be applied using a notched trowel. PA-828 may also be used alternatively to PA-1021 as a mastic for setting all metal flanges and drain lead flashings.

### **Product Approvals**

PA-828 Flashing Cement meets or exceeds the requirements of ASTM D 4586 Type II for asbestos free, asphalt based roof cement.

### **COMMERCIAL PRODUCT INFORMATION**

---

Unit: 5-Gallon Pail  
4.7 gallons (17.8 liters) net content

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 36 in X 48 in (91 cm X 122 cm) wooden pallet  
Number Pails Per Pallet: 36  
Number Pallets Per Truckload: 22  
Weight Per Pail: 51 lb (23 kg)

Shipping Classification: White Label (combustible)

Storage and Handling: All containers of PA-828 Flashing Cement should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 9/08