

# PARABASE PLUS



## Commercial Product Data Sheet

### Product Description

Parabase Plus is a lightly modified asphalt coated fiberglass base sheet or base ply. Parabase Plus consists of a lightweight random fibrous glass mat impregnated and coated with a modified blend of styrene butadiene-styrene (SBS) and asphalt.

### Product Uses

Parabase Plus is designed for use under guaranteed Siplast Roof Systems in certain nailable applications. Parabase Plus can also be used as a ply sheet in certain guaranteed Siplast Roof Systems. In nailable applications, Parabase Plus is lapped 3 inches (7.6 cm) at sides and 6 inches (15.2 cm) at ends, and is mechanically fastened according to Siplast requirements. In mopping applications, Parabase Plus is lapped 3 inches (7.6 cm) sides and ends, and is applied in approved Type IV asphalt.

### Product Approvals

Parabase Plus is approved by FM Approvals (FM Standard 4470) for use as a nailed base sheet in Siplast Paradiene 20/30, Veral, and Parafor 50 LT non-insulated lightweight concrete roof deck constructions, subject to FM conditions and limitations.

Parabase Plus has been classified by Underwriters Laboratories as a  $cUL_{us}$  rated G2 Base Sheet. Parabase Plus is approved by Underwriters Laboratories for use in UL Classified Siplast Paradiene 20/30, Paradiene 20/30 FR, Veral, Paradiene 40 FR, and Paratech FR Roof Systems. Contact Siplast for specific  $cUL_{us}$  Classified roof systems using Parabase Plus.

Siplast Roof Systems also have received the approval of many regional and local authorities. Please contact Siplast for specific information as required.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 9/08

### COMMERCIAL PRODUCT INFORMATION

Unit:	Roll		
Coverage:	3 Squares	(27.9 m <sup>2</sup> )	
Coverage Weight Per Square:	Min:	30 lb	(1.4 kg/m <sup>2</sup> )
Roll Length:	Min:	102.3 ft	(31.2 m)
Roll Width:	Avg:	3.28 ft	(1.00 m)
Thickness:	Avg:	47 mils	(1.2 mm)
	Min:	39 mils	(1.0 mm)
Top Surfacing:	Silica Parting Agent		
Back Surfacing:	Silica Parting Agent		

Lines: Two laying lines are placed 3 in (7.6 cm) and 13 5/8 in (34.6 cm) from each edge of the material. The line color for this material is blue.

Packaging: The palletted material is protected by a heat shrink polyethylene shroud.

Pallet: 41 in X 48 in (104 cm X 122 cm) wooden pallet  
Number Rolls Per Pallet: 20  
Number Pallets Per Truckload: 18  
Minimum Roll Weight: 90 lb (40.8 kg)

Storage and Handling: All Siplast roll roofing products should be stored on end on a clean flat surface. Care should be taken that rolls are not dropped on ends or edges and are not stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing should be stored in a dry place, out of direct exposure to the elements, and should not be double stacked. Material should be handled in such a manner as to ensure that it remains dry prior to and during installation.