

# PRO CHIPS



## Commercial Product Data Sheet

---

### **Product Description**

Pro Chips are flat, angular pigmented polymer flakes suitable for broadcast.

### **Product Uses**

Pro Chips are broadcast into the finish layer of Pro Color Finish reinforced and unreinforced Terapro Waterproofing and Surfacing Systems and Parapro Roof Membrane Systems to achieve a textured, decorative surface.

### **Color**

Pro Chips are supplied in black and white. Colors are mixed for application.

### **Size**

Pro Chips size: 0.3 - 1.6 mm

### **Packaging**

Pro Chips are supplied in 2-kg (4.4 lb) resealable drums with locking ring.

### **Coverage Rate**

Approximate consumption: 0.06 kg/m<sup>2</sup> (0.0056 kg/sf)

See recommendations for specific applications.

### **Application**

Pro Chips are broadcast into the Pro Color Finish of reinforced and unreinforced Terapro Waterproofing and Surfacing Systems and Parapro Membrane Systems before the color finish layer of catalyzed resin sets. Pro Chips are broadcast randomly, without solidly covering of the wearing layer. Pro Chips can be applied by hand or with a mechanical applicator. After the color finish layer of resin is set, any loose Pro Chips may be removed by blowing with oil-free compressed air or vacuum and collected for later use.

### **Storage:**

Store in closed containers on a clean, flat surface. Containers should not be dropped, and container seals should not be broken prior to use. Store in a dry place, out of direct exposure to the elements.

### **Handling**

Avoid generating dust. Consult the Material Safety Data Sheet (MSDS) for additional information pertaining to this product.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 9/08