

# ZONO-TITE FASTENER



## Commercial Product Data Sheet

### Product Description

The Siplast Zono-tite Fastener is formed from one piece of specially coated galvanized steel. The split-wedge leg spreads upon installation into lightweight insulating concrete to provide pullout resistance. Zono-tite Fasteners are assembled with a corrosion resistant Galvalume stress distribution plate for increased wind uplift resistance.

### Product Uses

Zono-tite Fasteners are engineered to secure base sheets to lightweight insulating concrete. Properly installed, Zono-tite Fasteners provide wind uplift resistance to meet Factory Mutual and Underwriters Laboratories requirements.

### Product Approvals

Zono-tite Fasteners are approved by Factory Mutual Approval Standard Class No. 4454. Contact Siplast for specific approvals on product use and approved nailing patterns.

### COMMERCIAL PRODUCT INFORMATION

Unit Length: Nominal 1.7 inches (4.3 cm)

Plate Size: 2.7 inches (6.9 cm)

Color: Black fastener with attached silver/grey plate

Quantity: 1,000/Box

Packaging: The fasteners are packaged in corrugated cardboard boxes. The boxes are stacked 3 high on wooden pallets and stretch wrapped.

Box Size: 14 in X 14 in X 23 in  
(35 cm X 35 cm X 58 cm)

Pallet: 44 in X 44 in (112 cm X 112 cm)

Number Boxes Per Pallet: 18

Number Pallets Per Truckload: 60

Shipping Weight Per Box: 40 lb (18.1 kg)

Fastener Head Stamped: Z-T

Storage and Handling: All boxes should be stored upright on a clean, flat surface. Boxes should be stored in a dry place, out of direct exposure to the elements. All materials should be handled in such a manner as to ensure that they remain dry prior to and during installation.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).

Rev 10/07 (ZTBSA 175)