












## Parafast Reference Chart

	Parafast Product	Use	Available Lengths/ Diameters	Quantity Per Package
	<b>Roofing Fastener</b>	For conventional steel, wood, and plywood decks. Use with Parafast 3" Metal Plate.	1½" - 8"	1,000/pail
	<b>3" Metal Plate</b>	For use with Parafast Roofing Fasteners, Parafast HD Fasteners, Parafast XHD Fasteners, and Parafast CD-10 Fasteners.	3" diameter	1,000/pail
	<b>PA (Pre-assembled) Fastener and 3" Metal Plate</b>	For steel, wood, and plywood decks.	Fastener: 2" - 8" Plate: 3" diameter	250/box
	<b>HD Fastener</b>	For heavy steel and concrete decks. Use with Parafast 3" Metal Plate.	1¼" - 18"	Quantity per package varies with fastener size.
	<b>XHD Fastener</b>	For specialty applications. Use with Parafast 3" Metal Plate.	2" - 18"	Quantity per package varies with fastener size.
	<b>CD-10 Fastener</b>	Concrete drive fastener for structural concrete decks. Use with standard Parafast 3" Metal Plate.	2" - 12"	Quantity per package varies with fastener size.
	<b>LD Fastener</b>	For gypsum and cementitious wood fiber decks. Use with LD 3" Metal Plate.	2½" - 12"	Quantity per package varies with fastener size.
	<b>LD 3" Metal Plate</b>	For use with Parafast LD Fastener on gypsum and cementitious wood fiber decks.	3" diameter	500/box
	<b>Zono-tite Fastener</b>	Base sheet fastener for use with lightweight insulating concrete	1.7"	1,000/box
	<b>NVS Fastener</b>	Base sheet fastener for use with lightweight insulating concrete.	1"	1,000/box
	<b>Para-Lok Fastener</b>	Base sheet fastener for use with cementitious wood fiber and gypsum decks.	1.4" and 1.8"	500/box