



MATERIAL SAFETY DATA SHEET

HMIS

H = 1

F = 0

R = 0

PPE = See Section 8

VOC: 0 grams per liter

Section I

Manufacturer: Siplast, an Icopal Group Company
880-643-1591 or 800-922-8800
Address: 1000 E. Rochelle Blvd., Irving, TX 75062
Emergency Phone No.: CHEMTREC, (800) 424-9300 (U.S.), (703) 527-3887 (outside of U.S.)
Product Class: Roof Coating
Trade Name: PC-227 Elastomeric Roof Coating

Section II - Ingredients

Not known at hazardous level

Section III - Physical Data

Appearance: Milky white liquid
Boiling Point: 212°F
Evaporation Rate: Less than 1
Vapor Density (Air = 1): Less than 1
% Volatile by Volume: 40-55%
Weight per gallon: 11-12 lbs.
Vapor Pressure: Greater than 1

Section IV - Fire and Explosion Data

DOT Category: Not DOT regulated.
Flash Point: Non combustible
LEL %: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined space without proper protective gear, including self-contained breathing apparatus to protect against the hazardous effects of the normal products of combustion or oxygen deficiency.
Special Fire & Explosion Hazards: None

Section V - Health Hazard Data

EYES: Possibly slightly irritating to eyes with direct contact.
SKIN: Possible skin irritant with repeated or prolonged contact.
INHALATION: Vapor or mist can cause irritation of the nose, throat, and lungs.

Emergency and First Aid Procedures:
SKIN: Wash affected skin areas with soap and water.
EYES: Flush eyes with large amounts of water for at least 15 minutes. See physician if irritation persists.
INHALATION: Move subject to fresh air.
INGESTION: If swallowed, give two glasses of water to drink. See a physician.

Section VI - Reactivity Data

Stability: Stable X Unstable _____
Conditions to Avoid: Keep from freezing.
Hazardous Decomposition Products: Acrylic monomers.
Hazardous polymerization: Will not occur.
Incompatibility: None reasonably foreseeable.

Section VII - Spill or Leak Procedures

Steps to be taken: Keep spectators away. Floor may be slippery, use care to avoid falling. Scoop or shovel solid material into a suitable container for recovery or disposal. Keep spills out of municipal sewers and open bodies of water.
Waste Disposal Methods: Disposal should be in accordance with federal, state, and local regulations.

Section VIII - Special Protection Information

Respiratory Protection: Wear suitable respirator (MSHA/NIOSH approved or equivalent) where exposure limits are exceeded.
Ventilation: Normal use of this product at a jobsite does not require special ventilation. Mechanical exhaust ventilation is required when product is used or a large spill occurs in an interior confined space.
Eye Protection: Chemical splash goggles (ANSI Z-87.1 or approved equivalent)
Protective Gloves: Impervious

Section IX - Special Precautions

Precautions to be taken in handling and storage:
Keep from freezing.

Other precautions: None

The information and recommendations contained herein are, to the best of Siplast's knowledge and belief, accurate and reliable as of the date issued. Siplast does not warrant or guarantee their accuracy or reliability, and should not be liable for any loss or damage arising out of the use thereof. User should satisfy himself that he has all current data relevant to his particular use.