

PA-1125 PRIMER



Commercial Product Data Sheet

Product Description

PA-1125 Primer is an asphalt solvent blend designed to prepare metal, concrete, and masonry surfaces prior to application of bituminous Siplast Roofing and Flashing Systems.

Product Uses

PA-1125 Primer is applied to metal flanges, concrete, and masonry surfaces; the primer should be allowed to dry thoroughly prior to application of Siplast Roofing and Flashing Systems. PA-1125 Primer can be applied by roller brush or spray. Do not dilute or cut PA-1125 Primer with solvents. Diluting PA-1125 using petroleum solvents will affect its bonding and drying characteristics.

Product Approvals

PA-1125 meets or exceeds ASTM D 41 requirements for asphalt primer used in roofing and waterproofing.

VOC content: This product contains an average 393 g/l VOC.

COMMERCIAL PRODUCT INFORMATION

Unit: 5-Gallon Pail
4.7 gallons (17.8 liters) net content

Coverage: Coverage is dependent on the condition of the surface receiving the primer. The coverage ranges from 100 square feet per gallon (0.4 liter per 1/m²) on very rough, porous surfaces to 400 square feet per gallon (1.6 l/m²) on smooth, low-absorptive surfaces.

Flash Point, Pensky-Martens Closed Cup: 100°F (38°C)

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 45 in X 48 in (114 cm X 122 cm) wooden pallet
Number Pails Per Pallet: 42
Number Pallets Per Truckload: 22
Weight Per Pail: 37 lb (16.8 kg)

Shipping Classifications: White Label (combustible)

Storage and Handling: All containers of PA-1125 Primer should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 5/2018