

PARABASE FS



Commercial Product Data Sheet

Product Description

Parabase FS is a non-porous fiberglass base sheet designed for use under guaranteed Siplast Roof Systems in certain nailable applications. Parabase FS consists of a lightweight random fibrous glass mat impregnated and coated with a specially formulated, high quality, oxidized asphalt, and a polyolefin film backing.

Product Uses

In nailable applications, Parabase FS is lapped 3 inches (7.6 cm) at sides and 3 inches (7.6 cm) at ends and is mechanically fastened according to Siplast requirements.

Product Approvals

Parabase FS meets or exceeds the requirements of ASTM D 4601 Type II for asphalt coated, fiberglass base sheets.

Parabase FS is approved by FM Approvals (FM Standard 4470) for use as a nailed base sheet in Siplast Paradiene 20/30, Veral, and Parafor 50 LT non-insulated lightweight concrete roof deck constructions, subject to FM conditions and limitations.

Parabase FS has been classified by Underwriters Laboratories as a cUL_{us} rated G2 Base Sheet. Parabase FS is approved by Underwriters Laboratories for use in UL Classified Siplast Paradiene 20/30, Paradiene 20/30 FR, Veral, Paradiene 40 FR, and Paratech FR Roof Systems. Contact Siplast for specific cUL_{us} Classified roof systems using Parabase FS.

Siplast Roof Systems also have received the approval of many regional and local authorities. Please contact Siplast for specific information as required.

COMMERCIAL PRODUCT INFORMATION

Unit:	Roll		
Coverage:	3 Squares	(27.9 m ²)	
Coverage Weight Per Square:	Min: 20 lb	(0.9 kg/m ²)	
Roll Length:	Min: 108 ft	(32.9 m)	
Roll Width:	Avg: 3.0 ft	(0.91 m)	
Thickness:	Avg: 47 mils	(1.2 mm)	
	Min: 39 mils	(1.0 mm)	

Top Surfacing: Silica Parting Agent

Back Surfacing: Polyolefin film

Lines: Two laying lines are placed 3 in (7.6 cm) and 12.5 in (31.8 cm) from each edge of the material. The line color for this material is yellow.

Packaging: The palletted material is protected by a heat shrink polyethylene shroud.

Pallet: 40 in X 48 in (101.6 cm X 122 cm) wooden pallet
Number Rolls Per Pallet: 20
Number Pallets Per Truckload: 18
Minimum Roll Weight: 60 lb (27.2 kg)

Storage and Handling: All Siplast roll roofing products should be stored on end on a clean flat surface. Care should be taken that rolls are not dropped on ends or edges and are not stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing should be stored in a dry place, out of direct exposure to the elements, and should not be double stacked. Material should be handled in such a manner as to ensure that it remains dry prior to and during installation.

Rev 2/2018

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.