

# PARABLOCK TAPE



## Commercial Product Data Sheet

---

### ***Product Description***

Parablock Tape is used to secure the laps of Siplast Parablock Root Barrier. It is made from a cast polyethylene film coated with a high-tack synthetic elastomeric adhesive. The sealing tape resists moisture, cold temperature, and UV light.

### ***Application Guidelines***

Prior to installation of the Parablock Tape, wipe clean the lap area to be covered to ensure removal of all moisture, dirt, dust, or other contaminants that may otherwise inhibit full adhesion of the Parablock Tape. Remove release liner, center the width of the tape over the leading edge of the overlapping sheet and press the tape firmly, facilitating full contact between the tape adhesive and root barrier surface.

### **COMMERCIAL PRODUCT INFORMATION**

---

#### ***Physical Properties***

Unit: Roll  
Thickness: 2 mils  
Roll Width: 4 inches (101.6 mm)  
Roll Length: 100 feet (30.49 m)  
Roll Weight: 5.3 lb (2.4 kg)  
Color: Black (Optional in Gray)

#### ***Mechanical Properties***

Thickness: 25 ± 2 mils  
Tensile Strength: PSI 4500 ± 500  
Elongation %: 700 ± 100  
Application Temperature: 41°F - 122°F

#### ***Packaging***

Rolls are provided in case quantities.  
Rolls per case: 6  
Palletization: 60 cases per pallet

#### ***Storage and Handling***

Parablock Tape must be stored in a dry location out of direct exposure to the elements. Do not stack other materials on the tape.

1 year shelf life

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

Rev 10/2018