

# PARAGLAS



## Commercial Product Data Sheet

### Product Description

Paraglas is an asphalt-coated fiberglass ply sheet. Paraglas consists of a lightweight random fibrous glass mat impregnated and coated with a specially formulated, high quality, oxidized asphalt.

### Product Uses

Paraglas is designed for use in conjunction with sheathing paper under guaranteed Siplast Roof Systems in certain nailable applications. Paraglas can also be used as a ply sheet in certain guaranteed Siplast Roof Systems. When used as a base sheet, Paraglas is placed over sheathing paper and is lapped 4 inches (10.2 cm) at sides and 6 inches (15.2 cm) at ends, and is mechanically fastened according to Siplast requirements. When used as a ply sheet, Paraglas is applied in approved Type IV asphalt and lapped 3 inches (7.6 cm) side and end.

### Product Approvals

Paraglas meets or exceeds the requirements of ASTM D 2178 Type IV and Federal Specification SS-R-620B Type III for asphalt coated, fiberglass ply sheets.

Siplast Roof Systems also have received the approval of many regional and local authorities. Please contact Siplast for specific information as required.

### COMMERCIAL PRODUCT INFORMATION

Unit:	Roll		
Coverage:	5 Squares	(50.2 m <sup>2</sup> )	
Coverage Weight Per Square:	Min: 6.8 lb	(0.3 kg/m <sup>2</sup> )	
	Avg: 9.0 lb	(0.38 kg/m <sup>2</sup> )	
Roll Length:	Min: 180 ft	(54.9 m)	
Roll Width:	Avg: 3.0 ft	(0.91 m)	
Thickness:	Avg: 30 mils	(0.8 mm)	

Lines: Two laying lines are placed 4 in (10.2 cm) and 11.5 in (29.2 cm) from each edge of the material. Two laying lines are also placed 1.5 inch (3.8 cm) from the center of the sheet. The line color for this material is white.

Packaging: The palletted material is protected by a heat shrink polyethylene shroud.

Pallet: 40 in X 48 in (101.6 cm X 122 cm) wooden pallet  
Number Rolls Per Pallet: 20  
Number Pallets Per Truckload: 18  
Minimum Roll Weight: 34 lb (15.4 kg)

Storage and Handling: All Siplast roll roofing products should be stored on end on a clean flat surface. Care should be taken that rolls are not dropped on ends or edges and are not stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing should be stored in a dry place, out of direct exposure to the elements, and should not be double stacked. Material should be handled in such a manner as to ensure that it remains dry prior to and during installation.

2/2018

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).