

Commercial Product Data Sheet

Product Description

Pro Tape is a specialty, self-adhesive stripping ply accessory for use in conjunction with the Paraflex Metal Roof Coating Systems. Pro Tape consists of a reinforcing fabric laminated to a polymer-based self-adhesive blend, with the back surface lined with a siliconized release paper.

Product Uses

Pro Tape is a self-adhesive product used to reinforce joints/seams, transitions, and penetrations prior to application of Paraflex Liquid Flashing Membrane. Contact Siplast for specific information on substrate qualification/preparation as well as product uses and application.

Packaging

Pro Tape is packaged in the following roll dimension:

WIDTH	LENGTH	COVERAGE
6 inches (152 mm)	50 feet (15.2 meters)	25 ft ² (2.32 m ²)
2 inches (50.8 mm)	50 feet (15.2 meters)	8.33 ft ² (0.774 m ²)

Properties

Tensile Strength (min)	850 psi	ASTM D2370
Elongation (min)	1000%	ASTM D2370
Permeance (max)	0.001 perms	

Application Conditions

Do not apply when substrate or ambient temperatures are below 32°F or above 110°F (0°C to 110°C).

Initial bond is immediate will full bond strength at 24-hours.

Service Temperature Limits: -30°F to 180°F (-35°C to 82°C)

Commercial Product Information

6-inch Tape

Unit: Box

Coverage: 25 ft² (2.32 m²)

Packaging: Rolls are wound onto a compressed paper tube and boxed 4-per box. The rolls are sold only in box quantities.

Roll weight: 6 lb (2.72 kg)

Number Rolls Per Pallet: 96

2-inch Tape

Unit: Box

Coverage: 25 ft² (2.32 m²)

Packaging: Rolls are wound onto a compressed paper tube and boxed 12-per box. The rolls are sold only in box quantities.

Roll weight: 21 lb (9.53 kg)

Number Rolls Per Pallet: 288

Storage

Always store in a cool and dry location, away from direct sunlight. Material should be handled in such a manner as to ensure that it remains dry prior to and during installation. Shelf life is 12-months from date of shipment.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 6/2018