

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

### SECTION 1. IDENTIFICATION

Product name : Pro Catalyst Powder

#### Manufacturer or supplier's details

Company name of supplier : Siplast

Address : 11491 Quorum Dr., Suite 600  
Dallas, TX 75254  
USA

Telephone : +1-800-922-8800

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300  
CHEMTREC WORLD (24h): +1-703-527-3887

#### Recommended use of the chemical and restrictions on use

Recommended use : Hardener

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Organic peroxides : Type D  
Eye irritation : Category 2B  
Skin sensitization : Category 1  
Reproductive toxicity : Category 1B  
Short-term (acute) aquatic hazard : Category 1  
Long-term (chronic) aquatic hazard : Category 1

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version  
3.0

Revision Date:  
10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

### Precautionary Statements

H320 Causes eye irritation.  
H360D May damage the unborn child.  
H410 Very toxic to aquatic life with long lasting effects.

#### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.  
P234 Keep only in original container.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P391 Collect spillage.

#### Storage:

P405 Store locked up.  
P410 Protect from sunlight.  
P411 + P235 Store at temperatures not exceeding < 30 °C/ < 86 °F. Keep cool.  
P420 Store away from other materials.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

Chemical nature : Organic Peroxide  
Solid mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Dicyclohexyl phthalate	84-61-7	>= 50 - < 55
Dibenzoyl peroxide	94-36-0	>= 45 - < 50

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.  
Call a physician immediately.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
If breathed in, move person into fresh air.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
If on skin, rinse well with water.  
If on clothes, remove clothes.  
If symptoms persist, call a physician.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Call a physician immediately.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes eye irritation.  
May damage the unborn child.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version  
3.0

Revision Date:  
10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

- Suitable extinguishing media : Water spray jet  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.
- The product burns violently.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
The product will float on water and can be reignited on surface water.  
Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.  
Remove undamaged containers from fire area if it is safe to do so.  
Use water spray to cool unopened containers.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Remove all sources of ignition.  
Follow safe handling advice and personal protective equipment recommendations.  
Never return spills in original containers for re-use.  
Treat recovered material as described in the section "Disposal considerations".
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## PRO CATALYST POWDER

Version  
3.0

Revision Date:  
10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.  
Clear spills immediately.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
To clean the floor and all objects contaminated by this material, use plenty of water.  
Soak up with inert absorbent material.  
Isolate waste and do not reuse.  
Non-sparking tools should be used.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on protection against fire and explosion : Avoid dust formation.  
Provide appropriate exhaust ventilation at places where dust is formed.  
Keep away from heat and sources of ignition.  
Use only explosion-proof equipment.  
Keep away from combustible material.

Advice on safe handling : Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Take precautionary measures against static discharges.  
Never return any product to the container from which it was originally removed.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Avoid confinement.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash thoroughly after handling.  
For personal protection see section 8.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.  
Electrical installations / working materials must comply with the technological safety standards.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in original container.

## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

Keep containers tightly closed in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 30 °C

< 86 °F

Further information on storage stability : No decomposition if stored normally.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dibenzoyl peroxide	94-36-0	TWA	5 mg/m <sup>3</sup>	ACGIH
		TWA	5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	OSHA P0

Engineering measures : Minimize workplace exposure concentrations.

## Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : Filter type P

## Hand protection

Material : butyl-rubber

Break through time : >= 480 min

Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles  
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.  
Ensure that eyewash stations and safety showers are close to the workstation location.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version  
3.0

Revision Date:  
10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
- Hygiene measures : Keep away from food and drink.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Color : white
- Odor : aromatic
- pH : No data available
- Melting point/range : Decomposition: Decomposes below the melting point.
- Boiling point/boiling range : Not applicable
- Flash point : Not applicable
- Flammability (solid, gas) : Not applicable
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : No data available
- Density : No data available
- Solubility(ies)
- Water solubility : insoluble
- Solubility in other solvents : Solvent: Phthalates  
Description: soluble
- Self-Accelerating decomposition temperature (SADT) : 60 °C  
Method: UN-Test H.4  
SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
- Viscosity
-

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0      Revision Date: 10/26/2021      Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

Viscosity, dynamic : Not applicable  
Viscosity, kinematic : No data available  
Explosive properties : Not explosive  
Oxidizing properties : The substance or mixture is not classified as oxidizing.  
Organic peroxide

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.  
Chemical stability : Stable under recommended storage conditions.  
Possibility of hazardous reactions : Dust may form explosive mixture in air.  
Conditions to avoid : Protect from contamination.  
Contact with incompatible substances can cause decomposition at or below SADT.  
Heat, flames and sparks.  
Avoid confinement.  
Incompatible materials : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents  
Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Dicyclohexyl phthalate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Assessment: The substance or mixture has no acute oral toxicity  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

##### Dibenzoyl peroxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral tox-



# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

icity

Acute inhalation toxicity : LC50 (Rat): > 24.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Remarks: No data available

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Product:**

Remarks : May cause skin irritation in susceptible persons.

#### **Components:**

##### **Dicyclohexyl phthalate:**

Result : No skin irritation

##### **Dibenzoyl peroxide:**

Species : Rabbit  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Causes eye irritation.

#### **Product:**

Remarks : Product dust may be irritating to eyes, skin and respiratory system.

#### **Components:**

##### **Dicyclohexyl phthalate:**

Result : No eye irritation

##### **Dibenzoyl peroxide:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 7 days

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0      Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

### **Product:**

Remarks : Causes sensitization.

### **Components:**

#### **Dicyclohexyl phthalate:**

Routes of exposure : Skin contact  
Species : Mouse  
Result : May cause sensitization by skin contact.

#### **Dibenzoyl peroxide:**

Routes of exposure : Skin contact  
Species : Mouse  
Method : Local lymph node assay (LLNA)  
Result : May cause sensitization by skin contact.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Dicyclohexyl phthalate:**

Genotoxicity in vitro : Result: negative  
Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Remarks: No data available

#### **Dibenzoyl peroxide:**

Genotoxicity in vitro : Result: negative  
Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: negative  
Remarks: In vivo tests did not show mutagenic effects

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Dicyclohexyl phthalate:**

Remarks : This information is not available.

#### **Dibenzoyl peroxide:**

Remarks : Not classified due to data which are conclusive although insufficient for classification.

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

May damage the unborn child.

#### **Components:**

##### **Dicyclohexyl phthalate:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.  
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

##### **Dibenzoyl peroxide:**

Effects on fertility : Species: Rat, male  
Application Route: Oral  
General Toxicity Parent: NOAEL: 1,000 mg/kg body weight  
Method: OECD Test Guideline 422

Species: Rat, female  
Application Route: Oral  
General Toxicity Parent: NOAEL: 500 mg/kg body weight  
Method: OECD Test Guideline 422

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

### **STOT-single exposure**

Not classified based on available information.

#### **Components:**

##### **Dibenzoyl peroxide:**

Routes of exposure : Ingestion  
Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### **STOT-repeated exposure**

Not classified based on available information.

#### **Components:**

##### **Dibenzoyl peroxide:**

Routes of exposure : Ingestion  
Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

### Repeated dose toxicity

#### Components:

##### Dicyclohexyl phthalate:

Species : Rat  
NOAEL : 50 mg/kg  
Application Route : Ingestion  
Exposure time : 90 d  
Method : OECD Test Guideline 408

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### Dibenzoyl peroxide:

No aspiration toxicity classification

### Further information

#### Product:

Remarks : No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Dicyclohexyl phthalate:

Toxicity to fish : LC50 (*Oryzias latipes* (Orange-red killifish)): > 2 mg/l  
Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : NOEC (*Daphnia magna* (Water flea)): > 2 mg/l  
Exposure time: 48 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 2 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 0.181 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEC: > 100 mg/l  
Exposure time: 3 h  
Test Type: Respiration inhibition

## PRO CATALYST POWDER

Version  
3.0Revision Date:  
10/26/2021Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

Method: OECD Test Guideline 209

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Dibenzoyl peroxide:**Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.11 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.06 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.001 mg/l  
Exposure time: 21 d  
Test Type: semi-static test  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 10

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l

**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability****Components:****Dicyclohexyl phthalate:**

Biodegradability : Result: Readily biodegradable.

**Dibenzoyl peroxide:**

Biodegradability : Result: Inherently biodegradable.

**Bioaccumulative potential****Components:****Dicyclohexyl phthalate:**

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

Partition coefficient: n-octanol/water : log Pow: 4.82 (25 °C / 25 °C)

### Dibenzoyl peroxide:

Partition coefficient: n-octanol/water : log Pow: 3.2 (20 °C / 20 °C)

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
Dispose of in accordance with local regulations.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3106  
Proper shipping name : ORGANIC PEROXIDE TYPE D, SOLID (DIBENZOYL PEROXIDE)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : 5.2

#### IATA-DGR

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

UN/ID No. : UN 3106  
Proper shipping name : Organic peroxide type D, solid  
(Dibenzoyl peroxide)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat  
Packing instruction (cargo aircraft) : 570  
Packing instruction (passenger aircraft) : 570

### IMDG-Code

UN number : UN 3106  
Proper shipping name : ORGANIC PEROXIDE TYPE D, SOLID  
(DIBENZOYL PEROXIDE)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : 5.2  
EmS Code : F-J, S-R  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3106  
Proper shipping name : Organic peroxide type D, solid  
(Dibenzoyl peroxide, <= 51%)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : ORGANIC PEROXIDE  
ERG Code : 145  
Marine pollutant : yes

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

**SARA 311/312 Hazards** : Organic peroxides  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Reproductive toxicity

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Dibenzoyl peroxide 94-36-0

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### The ingredients of this product are reported in the following inventories:

DSL (CA) : All components of this product are on the Canadian DSL

AICS (AU) : On the inventory, or in compliance with the inventory

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory



# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version 3.0  
Revision Date: 10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET



## PRO CATALYST POWDER

Version        Revision Date:  
3.0            10/26/2021

Date of last issue: 05/11/2018  
Date of first issue: 10/26/2016

---

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.  
These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/26/2021

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8