

1. Identification

Product identifier	STREETBOND COLORANT AQUA		
Other means of identification			
Product Code			
Recommended use	Colorant.		
Manufacturer/Importer/Supplier/Distributor information			
Distributor			
Company name	Siplast 1000 Rochelle Blvd. Irving, TX 75062 USA		
Telephone	1-800-922-8800		
Emergency phone number	CHEMTREC [DAY OR NIGHT]	1-800-424-9300	
	Within USA and CANADA	1-800-424-9300	
	Outside USA and Canada:	1 703-741-5970	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger	
Hazard statement	May cause cancer.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If exposed or concerned: Get medical advice/attention.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	40 to <50

Chemical name	Common name and synonyms	CAS number	%
Hydroxylated Silicon Dioxide		63231-67-4	5 to <10
IRON OXIDE		1309-37-1	5 to <10
Propylene Glycol		57-55-6	5 to <10
Manganese (III) Oxide		1317-34-6	1 to <5
Silicate		14807-96-6	1 to <5
Crystalline Silica - Quartz		14808-60-7	0.1 to <1
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable levels			30 to <40

4. First-aid measures

Inhalation	Not available.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
IRON OXIDE (CAS 1309-37-1)	PEL	10 mg/m ³	Fume.
Manganese (III) Oxide (CAS 1317-34-6)	Ceiling	5 mg/m ³	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	TWA	0.8 mg/m ³	
		20 mppcf	
Silicate (CAS 14807-96-6)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m ³	Respirable fraction.
Manganese (III) Oxide (CAS 1317-34-6)	TWA	0.1 mg/m ³	Inhalable fraction.
		0.02 mg/m ³	Respirable fraction.
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m ³	Inhalable fraction.
Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	TWA	6 mg/m ³	
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m ³	Dust and fume.
Manganese (III) Oxide (CAS 1317-34-6)	STEL	3 mg/m ³	Fume.
	TWA	1 mg/m ³	Fume.
Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	If contact is likely, safety glasses with side shields are recommended.
Skin protection	
Hand protection	For prolonged or repeated skin contact use suitable protective gloves.
Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Blue.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available
Initial boiling point and boiling range	Not available
Flash point	Not available
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available
Flammability limit - upper (%)	Not available
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	700 °F (371.11 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	15.55 lbs/gal
Flammability class	Not available
Percent volatile	55.84 %
Specific gravity	1.87
VOC	220.248978 g/l Regulatory estimated 1.838012 lbs/gal Regulatory estimated

124.255442 g/l Material estimated
1.036931 lbs/gal Material estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Hydroxylated Silicon Dioxide (CAS 63231-67-4)		
Acute		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Propylene Glycol (CAS 57-55-6)		
Acute		
Oral		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica - Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	3 Not classifiable as to carcinogenicity to humans.
IRON OXIDE (CAS 1309-37-1)	3 Not classifiable as to carcinogenicity to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Silica - Quartz (CAS 14808-60-7)

Known To Be Human Carcinogen.

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Known To Be Human Carcinogen.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Propylene Glycol (CAS 57-55-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propylene Glycol -0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Manganese (III) Oxide (CAS 1317-34-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Manganese (III) Oxide	1317-34-6	1 to <5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Manganese (III) Oxide (CAS 1317-34-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline Silica - Quartz (CAS 14808-60-7)
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)
Silicate (CAS 14807-96-6)
Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Crystalline Silica - Quartz (CAS 14808-60-7)
IRON OXIDE (CAS 1309-37-1)
Silicate (CAS 14807-96-6)
Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline Silica - Quartz (CAS 14808-60-7)
IRON OXIDE (CAS 1309-37-1)
Manganese (III) Oxide (CAS 1317-34-6)
Propylene Glycol (CAS 57-55-6)
Silicate (CAS 14807-96-6)
Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline Silica - Quartz (CAS 14808-60-7)
IRON OXIDE (CAS 1309-37-1)
Propylene Glycol (CAS 57-55-6)
Silicate (CAS 14807-96-6)
Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Manganese (III) Oxide (CAS 1317-34-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica - Quartz (CAS 14808-60-7)	Listed: October 1, 1988
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Revision date	5/03/2019
Version #	01
HMIS® ratings	Health: 1* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 0 Flammability: 0 Instability: 0

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. Siplast cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information Product and Company Identification: Converted to Siplast SDS