

1. Identification

Product identifier	STREETBOND COLORANT IRISH CREAM	
Other means of identification		
Product Code		
Recommended use	Colorant.	
Recommended restrictions	None.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Siplast 1000 Rochelle Blvd. Irving, TX 75062 USA	
Telephone	1-800-922-8800	
Emergency phone number	CHEMTREC [DAY OR NIGHT]	1-800-424-9300
	Within USA and CANADA	1-800-424-9300
	Outside USA and Canada:	1-703-741-5970

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Combustible dust	

Label elements



Signal word	Warning
Hazard statement	Suspected of causing cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Observe good industrial hygiene practices.
Response	If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	60 to <70
Propylene Glycol		57-55-6	5 to <10
Hydroxylated Silicon Dioxide		63231-67-4	1 to <5
IRON OXIDE		1309-37-1	1 to <5
Crystalline Silica - Quartz		14808-60-7	0.1 to <1
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable levels			20 to <30

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). Apply extinguishing media carefully to avoid creating airborne dust.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p>

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
IRON OXIDE (CAS 1309-37-1)	PEL	10 mg/m ³	Fume.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	TWA	0.8 mg/m ³	
		20 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m ³	Respirable fraction.
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m ³	Inhalable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline Silica - Quartz (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	TWA	6 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m ³	Dust and fume.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.
Individual protection measures, such as personal protective equipment	
Eye/face protection	If contact is likely, safety glasses with side shields are recommended.
Skin protection	
Hand protection	For prolonged or repeated skin contact use suitable protective gloves.
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	Cream.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.

Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	700 °F (371.11 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	16.75 lbs/gal
Flammability class	Not available.
Percent volatile	61.27 %
Specific gravity	2.01
VOC	282.71396 g/l Regulatory estimated 2.359292 lbs/gal Regulatory estimated 151.538576 g/l Material estimated 1.264613 lbs/gal Material estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Minimize dust generation and accumulation.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Hydroxylated Silicon Dioxide (CAS 63231-67-4)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Propylene Glycol (CAS 57-55-6)		
<u>Acute</u>		
Oral		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg

Components	Species	Test Results
	Rat	30 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Suspected of causing cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica - Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Hydroxylated Silicon Dioxide (CAS 63231-67-4)	3 Not classifiable as to carcinogenicity to humans.
IRON OXIDE (CAS 1309-37-1)	3 Not classifiable as to carcinogenicity to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Silica - Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Propylene Glycol (CAS 57-55-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Mummichog (Fundulus heteroclitus)
		> 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propylene Glycol -0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline Silica - Quartz (CAS 14808-60-7)

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Crystalline Silica - Quartz (CAS 14808-60-7)

IRON OXIDE (CAS 1309-37-1)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline Silica - Quartz (CAS 14808-60-7)

IRON OXIDE (CAS 1309-37-1)

Propylene Glycol (CAS 57-55-6)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline Silica - Quartz (CAS 14808-60-7)

IRON OXIDE (CAS 1309-37-1)

Propylene Glycol (CAS 57-55-6)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica - Quartz (CAS 14808-60-7)

Listed: October 1, 1988

Titanium Dioxide (CAS 13463-67-7)

Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Revision date	5/03/2019
Version #	01
Further information	Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
HMIS® ratings	Health: 1* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 0 Flammability: 2 Instability: 0
Disclaimer	This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. Siplast cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.
Revision Information	Product and Company Identification: Converted to Siplast SDS