

SAFETY DATA SHEET

1. Identification

Product identifier STREETBOND COLORANT WHITE

Other means of identification

Product Code

Recommended use Not available.

Manufacturer/Importer/Supplier/Distributor information

Distributor

Company name Siplast

1000 Rochelle Blvd. Irving, TX 75062 USA

Telephone 1-800-766-3411

CHEMTREC [DAY OR NIGHT] 1-800-424-9300 **Emergency phone number**

> Within USA and CANADA 1-800-424-9300 Outside USA and Canada: 1-703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Observe good industrial hygiene practices.

If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash Response

before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	60 to <70
Propylene Glycol		57-55-6	5 to <10
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable lev	vels		20 to <30

Material name: STREETBOND COLORANT WHITE

SDS US Version #: 01 Revision date: 5/03/2019

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.Eye contactDo not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDusts may irritate the respiratory tract, skin and eyes.

symptoms/effects, acute and

Indication of immediate medical attention and special treatment needed

delayed

media

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General informationIF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighter Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: STREETBOND COLORANT WHITE Version #: 01 Revision date: 5/03/2019

7. Handling and storage

Precautions for safe handling Obtain special

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

1/-1--

).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.
US. ACGIH Threshold Limit Values	:		
Components	Туре	Value	Form
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m ³	Inhalable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. Workplace Environmental Exp	osure Level (WEEL) Guides		
Components	Туре	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear suitable protective clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator

if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary,

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

SDS US

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.
Color Not available.
Odor Not available.

Material name: STREETBOND COLORANT WHITE

Version #: 01 Revision date: 5/03/2019 3 / 8

Odor threshold Not available. Not available. рH

Melting point/freezing point -74.2 °F (-59 °C) estimated Initial boiling point and boiling 370.76 °F (188.2 °C) estimated

range

210.0 °F (98.9 °C) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

2.6 % estimated

(%)

Flammability limit - upper

12.6 % estimated

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

2784.25 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 700 °F (371.11 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

16.99 lbs/gal Density

Combustible IIIB estimated Flammability class

Percent volatile 63 % Specific gravity 2.04

VOC 307.30751 g/l Regulatory estimated

> 162.872936 g/l Material estimated 2.564529 lbs/gal Regulatory estimated 1.3592 lbs/gal Material estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point. Conditions to avoid

Contact with incompatible materials. Minimize dust generation and accumulation.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Dust or powder may irritate the skin. Skin contact

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Material name: STREETBOND COLORANT WHITE

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results	
Propylene Glycol (CAS 57	-55-6)		
<u>Acute</u>			
Oral			
LD50	Guinea pig	18.4 g/kg	
	Mouse	23.9 g/kg	
	Rabbit	18 g/kg	
	Rat	30 g/kg	

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Propylene Glycol (CAS	S 57-55-6)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	710 mg/l, 96 hours
Titanium Dioxide (CAS	S 13463-67-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Material name: STREETBOND COLORANT WHITE

Version #: 01 Revision date: 5/03/2019

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propylene Glycol -0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Material name: STREETBOND COLORANT WHITE

Version #: 01 Revision date: 5/03/2019

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Propylene Glycol (CAS 57-55-6) Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Propylene Glycol (CAS 57-55-6) Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region Australia	Inventory name Australian Inventory of Chemical Substances (AICS)	On inventory (yes/no)* Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

16. Other information, including date of preparation or last revision

Revision date 5/03/2019

Version # 01

Further information Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the

Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

HMIS® ratings Health: 1*

Flammability: 2

Physical hazard: 0

NFPA ratings Health: 0

Flammability: 2 Instability: 0

Material name: STREETBOND COLORANT WHITE

Version #: 01 Revision date: 5/03/2019

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. Siplast cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to Siplast SDS

Material name: STREETBOND COLORANT WHITE SDS US 8/8