

MONARFLEX® SCAFFBAND PLUS FLAMESAFE

Commercial Product Data Sheet



Monarflex® Scaffband Plus Flamesafe reinforced scaffold sheeting is designed for use over scaffold or cable framework to provide temporary jobsite protection. The 210 g/m² strong reinforcement band is made of HDPE, with coated layers of LDPE containing fire-resistant additives. Each tape has pre-punched holes every 4 inches, making punching of the sheeting with the attachment accessory an easy task. For secure joining of the sheets, the outer 4-inch band is designed with a double row of pre-punched holes.

Contact Siplast for information on approved product uses.

USES: TEMPORARY ENCLOSURE

Properties	7'4"x137'	13'x100'
Color	White	White
Thickness (at scrim)	12 mils (0.30 mm)	12 mils (0.30 mm)
Coverage (Less Laps)	1004 sq ft	1300 sq ft
Tensile Strength	>75 lbs/in	>75 lbs/in
Pull Out Strength	>75 lbs	>75 lbs
Fire Properties	NFPA 701 (Test Method #2; Pass)	NFPA 701 (Test Method #2; Pass)
Light Transmission	Min. 50%	Min. 50%
Reinforcement Bands	3	5

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Installers Guide for detailed application information.

Storage and Handling

All Siplast Monarflex roll products should be stored on end on a clean, flat surface and should be stored in a dry place out of direct exposure to the elements. Materials stored on the job site during application should be kept on a pallet in a location that will protect the materials from rain or construction damage.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Rolls Per Crate: 30 of 7'4"
20 of 13'

Weight Per Roll: 40 lb (7'4")
52 lb (13')