

Parafast® 2 ¼" IR Plastic Plate

membrane seams and coverboards

Commercial Product Data Sheet

Description

Parafast® 2 ¼" IR Plastic Plate is a round, heavy-duty reinforced polymer plate with barbs, utilized for in-seam TPO membrane and coverboard preliminary securement, providing enhanced impact resistance.

Application

- In-seam attachment of 60 – 80 mil Parasolo® TPX™ with Parafast® XHD Fasteners, Parafast® RetroDrill Fasteners
- Preliminary securement of board stock with Parafast® Std. Fasteners, Parafast® #12 DF Fasteners, Parafast® #12 DP Fasteners, Parafast® HD Fasteners, Parafast® HD #14 Fasteners

Plate Material	Heavy-Duty Reinforced Polymer
Plate Diameter	2 ¼ in. (55.9 mm)
Packaging	500 pcs/Bucket
Weight	20 lb. (9.07 kg)
SKU	86S004



Parafast® 2 ¼" IR Plastic Plate




Plate Profile:

For best results, use a variable speed screw gun with a maximum of 2500 RPM. Higher RPM screw guns and impact drivers should not be used. To avoid overdriving and stripping the deck, ease off the trigger when tightening.

Listings, Approvals, and Certifications



- FM Approved, including Class 1 VSH- (Very Severe Hail) and SH- (Severe Hail) rated assemblies. Refer to RoofNav.com for specific assemblies.