



USES:
BASE PLY
BASE SHEET

PARABASE

Commercial Product Data Sheet

Parabase is an asphalt coated fiberglass base sheet or base ply. Parabase consists of a lightweight random fibrous glass mat impregnated and coated with a specially formulated, high quality, oxidized asphalt. Approved for use as a protection course in the PA-750 Hot Applied Rubberized Asphalt system.

Contact Siplast for information on approved product uses.

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information and slope limitations. Parabase is lapped 3 inches (76 mm) side and 6 inches (152.4 mm) end in nailable applications. In mopping applications, Parabase is lapped 3 inches (76 mm) side and end, and is applied in approved Type IV asphalt.



Storage and Handling

All Siplast roll roofing products should be stored on end on a clean, flat surface. Rolls should not be dropped on ends or edges or stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 40 in x 48 in (102 cm x 122 cm) wooden pallet
Rolls Per Pallet: 20
Pallets Per Truckload: 26
Minimum Roll Weight: 60 lb (27.2 kg)

Listings, Approvals, & Certifications



Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for specific assemblies.
FM Approved - Refer to RoofNav.com for specific assemblies.

| | |
|----------------------------|--|
| Standards | ASTM D4601 Type II |
| Roll Length | Min: 108 ft (32.9 m) |
| Roll Width | Avg: 3.0 ft (0.91 m) |
| Coverage | 3.0 Squares (27.9 m ²) |
| Coverage Weight Per Square | Min: 20 lb (0.9 kg/m ²) |
| Thickness | Avg: 47 mils (1.2 mm) Min: 39 mils (1.0 mm) |
| Laying Lines | 3 in (76 mm) & 12.5 in (317.5 mm) Line Color: White |
| Top Surfacing | Silica Parting Agent |
| Back Surfacing | Silica Parting Agent |

Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com