



# PARAFAST® ADHESIVE BAG-IN-BOX AND DRUMS

## Commercial Product Data Sheet

Parafast Adhesive is a fast-curing, two-component, low-rise foam adhesive used to adhere approved rigid insulation panels to substrates approved in advance by Siplast.

Contact Siplast for information on approved product uses.

**USES:  
RIGID INSULATION ADHESIVE**

Shelf Life	18 months (Unopened Product)
------------	---------------------------------

Temperature Limitations	Regular Grade	Winter Grade
Recommended Product Temp. at Time of Application	Min. 72°F (22°C)	Min. 72°F (22°C)
Ambient & Substrate Temp. Range at Time of Application	40°F (4.4°C) and rising	25°F – 65°F (3.9°C – 18°C)

## PRODUCT INFORMATION

### Application

Refer to the Siplast Para-Stik Insulation Adhesive & Parafast Adhesive Installers Guide for detailed application and yield/coverage information.

### Storage and Handling

Store Parafast Adhesive out of direct exposure to the elements at temperatures between 55°F and 85°F (13°C – 30°C). Do not allow Parafast Adhesive to freeze. Exposure to freezing temperatures may render the product unusable. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

### Packaging

#### Bag-in-Box

5-gal Bladder in Box (10 gal per A & B set)

Weight for Part A: 52 lb (23.6 kg); including packaging

Weight for Part B: 43 lb (19.5 kg); including packaging

Units Per Pallet (A or B): 32 (16 sets)

#### 15-Gallon Drums

15-gal Plastic Drums (30 gal per A & B set)

Weight for Part A: 162 lb (73.5 kg); including drum

Weight for Part B: 136 lb (61.7 kg); including drum

Units Per Pallet (A or B): 18 (9 sets)

### Listings, Approvals, & Certifications



Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at [www.siplast.com](http://www.siplast.com)  
Rev Date 4/2022