

PARAFAST® CD-10 FASTENER

Commercial Product Data Sheet

The Parafast CD-10 Fastener is a non-threaded, hammer-driven roofing fastener with CR-10 corrosion resistant coating. The Parafast CD-10 Fastener, in conjunction with the Parafast metal plates, is designed to secure roof insulation and substrate panels as well as Parasolo membranes to structural concrete roof decks.

Contact Siplast for information on approved product uses.

USES: ROOFING FASTENER

Split Bulb Diameter	0.270 / 0.277 in (6.83 / 7.03 mm)	
Head Height	0.115 in (3 mm)	
Head Diameter	0.435 in (11 mm)	
Head Style	Flat Top Pan Head	

Length	Product No.	Units/ Pkg	Box Weight
2 in	45S004	500	13 lb
3 in	45S116	500	18 lb
4 in	45S006	500	23 lb
5 in	45S008	500	28 lb
6 in	45S009	500	33 lb
7 in	45S010	500	38 lb
8 in	45S130	500	44 lb
9 in	45S131	250	25 lb
10 in	45S003	250	28 lb
11 in	45S128	250	31 lb
12 in	45S129	250	33 lb

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.





Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Corrugated Boxes (Various Sizes)

Listings, Approvals, & Certifications





Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com
Rev Date 2/2024