



PARAFAST® #12 DP FASTENER

Commercial Product Data Sheet

Parafast® #12 DP Fastener is a standard duty roofing screw coated with Tru-Kote™ Epoxy E-Coat. The Parafast #12 DP Fastener, in conjunction with the Parafast 3-inch Metal Plate, is designed to secure roof insulation and substrate panels and base sheets in approved assemblies to standard steel (16-22 gal), wood, and plywood roof decks.

Contact Siplast for information on approved product uses.

USES: ROOFING FASTENER

Head Diameter	0.438 in (11 mm)
Thread Diameter	0.214 in (5 mm)
Head Style	#3 Phillips Truss Head
Drive Bit	#3 Phillips Drive Bit Included

Length	Product No.	Thread Length	Units/ Pkg	Pkg Weight
1 5/8 in	45S248	Full	1000	13 lb
2 1/4 in	45S249	Full	1000	17 lb
3 in	45S250	Full	1000	21 lb
4 in	45S251	3-7/8 in	1000	26 lb
5 in	45S252	3-7/8 in	1000	32 lb
6 in	45S253	3-7/8 in	1000	38 lb
7 in	45S254	3-7/8 in	1000	44 lb
8 in	45S255	3-7/8 in	1000	50 lb

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.



Storage and Handling

All Siplast roofing products should be stored on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Plastic Pails (Various Sizes)

Listings, Approvals, & Certifications



FM Approved - Refer to RoofNav.com for specific assemblies.