

PARAFAST® METAL PLATES

Commercial Product Data Sheet

Parafast Metal Plates are stamped from Galvalume® coated steel. The design provides an even distribution of loads and eliminates sharp corners that can damage the rigid insulation or membrane. Parafast Metal Plates are designed to be used with Parafast Fasteners.

Contact Siplast for information on approved product uses.

ROOFING FASTENER

3" Tri-Rib Metal Plate					
Product No.	Size	Units/Pkg	Weight		
45S013	3 in (76 mm)	1000	32 lb		

3" Metal Plate for LD Fastener Only					
Product No.	Size	Units/Pkg	Weight		
45S042	3 in (76 mm)	500	19 lb		

Parafast 2 ¾" Barbed Plate					
Product No.	Size	Units/Pkg	Weight		
45S063	2 ¾ in (70 mm)	500	38 lb		

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information.

Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Parafast 3" Tri-Rib Plate Packaging: 6 gal Plastic Pail

Pallet: 48 in x 48 in (122 cm x 122 cm) wooden pallet

Pails Per Pallet: 32 Pallets Per Truckload: 24

Parafast LD Plate

Packaging: Corrugated Box 9.75 in x 9.75 in 7.75 in (24.77 cm x 24.77 cm x 19.69 cm)

Pallet: 48 in x 48 in (122 cm x 122 cm) wooden pallet

Parafast 2 ¾-inch Barbed Plate Packaging: 6 gal Plastic Pail

Pallet: 48 in x 48 in (122 cm x 122 cm) wooden pallet

Pails Per Pallet: 32

Listings, Approvals, & Certifications





Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at www.siplast.com Rev Date 10/2023