

# PARAFAST® TWIN-LOC FASTENER

## Commercial Product Data Sheet



Parafast® Twin-Loc Fasteners are factory preassembled units consisting of a tube, integral disk, and locking staple. The tube is fabricated from coated steel, the 2.7-inch disk is ribbed and is fabricated from coated steel, and the locking staple is fabricated from coated high-tensile steel wire. Parafast Twin-Loc Fasteners are designed to secure base sheets in approved assemblies to approved substrates.

Contact Siplast for information on approved product uses.

### USES: BASE SHEET FASTENER

Length	Product No.	Pieces/Box	Box Weight
1.4 in	45S287	500	26 lb
1.8 in	45S288	500	28 lb

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.

#### Storage and Handling

All Siplast roofing products should be stored upright on a clean, flat surface out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Pallet: 44 in x 44 in (112 cm x 112 cm)  
Boxes Per Pallet: 30

#### Listings, Approvals, & Certifications



FM Approved - Refer to RoofNav.com for specific assemblies.