

ParaGREEN™ Metal Edge Restraint, Extruded Aluminum

Commercial Product Data Sheet



Description:

ParaGREEN™ Metal Edge Restraint, Extruded Aluminum is a metal roof perimeter component specifically engineered and fabricated to be used with Siplast ParaGREEN™ Vegetated Roof Assemblies. It has a slotted base that facilitates drainage through the entire vegetated roof assembly, with standard factory formed corners.

Contact Siplast for information on approved product uses.

Uses: Vegetated Assemblies

Material	Aluminum Extruded 6063 Alloy
Thickness	0.063 in. 24 gauge
Finish*	Mill Finish Anodized
Length	8 ft.
Standard Heights	4.5 in. 6.5 in. 8.25 in.

*Black DuraFlex finish available by special order.

LEED Information
Recycled content varies from cast to cast and the specific recycled content within our products will vary as well. Contact Siplast for additional information.



Application:

Refer to the ParaGREEN™ Installation Guide for detailed application information.

Storage and Handling:

All Siplast ParaGREEN™ roofing products should be stored horizontally on a clean, flat surface.

ParaGREEN™ Extruded Aluminum Metal Edge must be stored in a dry location to prevent oxidation of the finish.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging:

Approx. Weight Per Piece: 20 – 30 lb. (9.07 kg – 13.61 kg)