

ParaGREEN™ Root Barrier Tape



With you every step of the way

Commercial Product Data Sheet

Description:

ParaGREEN™ Root Barrier Tape is used to secure the laps of ParaGREEN™ Root Barrier. It is made from a cast polyethylene film coated with a high-tack synthetic elastomeric adhesive. The sealing tape provides strong performance in conditions of moisture, cold temperatures, and exposure to UV light.

Contact Siplast for information on approved product uses.

Uses: Vegetated Accessory

Color	Black
Roll Width	4 in. (101.60 mm)
Roll Length	100 ft. (30.49 m)
Thickness	15 mils (0.38 mm)
Elongation	250%
Water Absorption	<0.30 wt%
Application Temperature	40°F – 185°F (-4°C – 85°C)

LEED Information

Recycled Content (% by weight)	Manufacture Location
0%	Houston, TX



Application:

Refer to the ParaGREEN™ Installation Guide for detailed application information.

Storage and Handling:

All Siplast ParaGREEN™ products should be stored on a clean, flat surface. The ParaGREEN™ Root Barrier Tape should be stored in a dry, well-ventilated area between 40°F – 140°F (4°C – 60°C). It is recommended that all components be stored between 68°F – 86°F (20°C – 30°C) for 24 hours prior to use for optimum product application. Do not stack other materials on the tape.

See product packaging for specific information on the safe handling of this product.