

PARASOLO™ PVC KEE 8” FLASHING STRIP

Commercial Product Data Sheet



Parosolo PVC KEE Flashing Strip is cut from reinforced Parosolo PVC KEE membrane and is used to “strip-in” field sheets and flashing details. Parosolo PVC KEE Flashing Strip can be used with both Parosolo PVC and Parosolo PVC KEE membrane systems.

Contact Siplast for information on approved product uses.


**USES:
PARASOLO PVC ACCESSORY**

Standards	ASTM D4434, Type II Standard Specification for Poly (Vinyl Chloride) Sheet Roofing
Thickness (nom.)	50 mils (1.27 mm)
Roll Size	8 in x 100 ft (20.3 cm x 30.5 m)
Roll Weight (nom.)	24 lb (11.8 kg)

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide and Siplast PVC Detail Manual for detailed information on application of Parosolo PVC KEE Flashing Strip. Parosolo PVC KEE Flashing Strip can be used in conjunction with both Parosolo PVC and PVC KEE membranes.



Storage and Handling

All Siplast roll roofing products should be stored on a clean, flat surface. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Rolls Per Wood Pallet: 64