

# Parasolo PVC Membrane Conditioner

## PVC Accessories



With you every step of the way

### Description:

Parasolo PVC Membrane Conditioner is a solvent used to clean exposed, contaminated, or aged PVC membrane surfaces prior to heat welding.

### Product Information:

<b>Color:</b>	Clear Liquid
<b>Container Size:</b>	1 gallon F-Style Can (3.78 L)
<b>Density @ 25°C:</b>	6.55 lb. per gallon (0.7844 g/mL)
<b>Flash Point:</b>	-4°F (-20°C) Closed Cup

### Storage and Handling:

Keep container closed when not in use. Store unopened containers in a cool, dry, and well-ventilated place away from heat and all ignition sources. See product packaging and the Safety Data Sheet (SDS) for specific information on the safe handling of this product.

### Packaging:

- Primary Packaging: F-Style Metal Can
- Weight per Can: 8 lb. (0.363 kg)
- 4 Cans per Carton
- DOT Classification: 1090, Class: 3, Flammable Liquid

### Application:

Refer to the applicable Siplast Technical Guide for detailed information on the use of Parasolo PVC Membrane Conditioner. Note that embedded dirt or contamination may require the use of an abrasive scrubbing pad and a low-residue cleaning solution such as Formula 409® prior to cleaning with Parasolo PVC Membrane Conditioner.

