

# TA-119<sup>®</sup> PRIMER

## Commercial Product Data Sheet



TA-119 Primer is a single component, water-based resinous primer designed for use with Siplast self-adhesive (SA) roofing and waterproofing membranes, TA-119 Primer is specifically formulated to condition masonry, wood, plywood, concrete, asphaltic, and gypsum surfaces to facilitate adhesion of Siplast SA and waterproofing membranes.

Contact Siplast for information on approved product uses.

**USES:**  
**NON-ASPHALTIC PRIMER**

Color	Milky Pink
Unit	5 gal pail 5 gal net content (18.9 L)
Shelf Life	1 year
Ambient Temp. at Point of Application	40°F – 105°F (4°C – 40°C)
Flash Point	>212°F (100°C)
VOC Content	< 50 g/L

### PRODUCT INFORMATION

#### Application

The rate of application may vary by substrate type and ambient conditions; see Substrate Table below for additional information.

Substrate	Approximate Coverage per Gallon ft <sup>2</sup> /gal (m <sup>2</sup> /L)	Approximate Gallons per Square (L/m <sup>2</sup> )
DensDeck	100 (2.46)	1.0 (0.4)
DensDeck Prime	200 (4.92)	0.5 (0.8)
USG Securock	200 (4.92)	0.5 (0.4)
Plywood	200 (4.92)	0.5 (0.4)
Concrete (Finish Grade)	400 (9.84)	0.25 (1.6)
Brick	100 (2.46)	1.0 (0.4)
CMU	100 (2.46)	1.0 (0.4)
Metal	400 (9.84)	0.25 (1.6)
Sanded SBS Sheet	200 (4.92)	0.5 (0.8)

#### Storage and Handling

All Siplast adhesive roofing products should be stored on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All roofing products should be stored in a dry place out of direct exposure to the elements and kept away from excessive heat, fire, or open flames.

Store at 45°F to 85°F (7°C to 29°C). Do not store in direct sunlight. Do not allow product to freeze. Improper storage may lead to product deterioration and render the product unusable.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Pallet: 44 in x 48 in (112 cm x 122 cm) wooden pallet  
 Pails Per Pallet: 24  
 Weight Per Pail: 48 lb (21.8 kg)