

TERAPRO™ PUR ACTIVATOR

Commercial Product Data Sheet



Terapro PUR Activator is a water soluble, organic solvent stripping agent. It is designed to increase the bond between existing polyurethane/polyuria coatings and other materials being applied onto them.

Contact Siplast for specific information on approved product uses.

USES: TERAPRO SYSTEM COMPONENT

Unit	1 gal can (3.79 L)
Application Rate	1,600 - 3,200 ft ² per gallon (0.5 to 1 mil WFT)
Coat window	1 hour
Dry Time	5-15 Minutes

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical or Installers Guide for detailed application information, including application/coverage rates. Product must be catalyzed before use.



Storage and Handling

Store indoors in a well-ventilated, cool, dry area away from heat, open fire, ignition sources, direct sunlight, oxidizing agents, strong acids, and strong alkalis. Do not open containers until ready to use. Partially filled containers should be purged of air using nitrogen blanketing and sealed tightly when not in use. Store jobsite materials on pallets in shaded, well-ventilated area. Standard shelf life is 24 months; product life is reduced when stored at temperatures 65°F to 90°F at (or below) 50% Relative Humidity.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Primary Packaging:
Weight Per Can: 7.5 lb (3.4 kg)