



# VERSASHIELD SOLO FIRE RESISTANT SLIP SHEET

## Commercial Product Data Sheet

Versashield SOLO Fire Resistant Slip Sheet is designed to be installed beneath roofing thermoplastic membranes to enhance resistance to exterior fire exposure.

Contact Siplast for information on approved product uses.

**USES:**  
PARASOLO TPO ACCESSORY

### PRODUCT INFORMATION

Roll Length (nom.)	166.7 ft (50.8 m)
Roll Width (nom.)	6 ft (1.83 m)
Coverage	10.0 Square (92.9 m <sup>2</sup> )

#### Application

Refer to the applicable Siplast Technical Guide and applicable Siplast details for information on the application of Versashield SOLO Fire Resistant Slip Sheets. Versashield SOLO Fire Resistant Slip Sheets are lapped 2 inches (51 mm) at sides and 4 inches (102 mm) at ends.

#### Storage and Handling

All Siplast roll roofing products should be stored on a clean, flat surface. All roofing products should be stored in a dry place out of direct exposure to the elements and double stacking is permissible. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Physical Properties			
Tensile	MD	40 lb/in (width min.)	ASTM D146/D858
Tensile	CMD	20 lb/in (width min.)	ASTM D146/D858
Tear	MD	300 g minimum	ASTM D1922
Tear	CMD	300 g minimum	ASTM D1922

#### Packaging

Pallet: 48 in x 74 in (122 cm x 188 cm) wooden pallet  
 Weight Per Roll: 110.2 lb (50 kg)  
 Rolls Per Pallet: 12 (4 rolls horizontally, 3 layers high)  
 Rolls Per Truck: 264  
 Pallets Per Truck: 22 (double stacked)

#### Listings, Approvals, & Certifications



Classified by UL in accordance with ANSI/UL 790. Refer to UL Product iQ for specific assemblies.