

# PENETRATION PORCELAIN PAVERS - IRMA

PORCELAIN PAVER ADHERED TO PAVER  
GRATE WITH APPROVED ADHESIVE

PAVER GRATE ON PEDESTALS

PEDESTAL SYSTEM

INSULATION

PARADRAIN DRAIN MAT  
(OPTIONAL)

SIPLAST WATERPROOFING  
MEMBRANE

6" MINIMUM  
8" RECOMMENDED

4"

4"

STRUCTURAL SUPPORT

SEALANT

SUBSTRATE

## NOTES:

1. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS AND SYSTEM SPECIFIC DETAILS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.
2. DESIGNER OF RECORD TO VERIFY CAPACITY OF DECK/SUBSTRATE TO ACCOMMODATE LOAD OF THE OVERBURDEN COMPONENTS.

CAUTION: SIPLAST RECOMMENDS THAT ALL PRACTICES PERTAINING TO INDUSTRY STANDARD TORCH SAFETY REQUIREMENTS AND GUIDELINES BE FOLLOWED. THIS INCLUDES PERFORMING A FIRE WATCH FOLLOWING ANY TORCH APPLICATIONS. ALWAYS HAVE APPROVED FIRE EXTINGUISHING EQUIPMENT NEARBY WHEN USING A TORCH.

Scale: NTS

REF: PENETRATION - PORCELAIN PAVERS - IRMA

Detail Number:  
DE-7407K2



14911 Quorum Drive, Suite 600 - Dallas, Texas - 75254 (800) 922-8800

[www.siplast.com](http://www.siplast.com)

Rev: 05.08.2024