

## Manufacturer Inventory

WALLcontrol™ Reinforced Aluminum AWB and  
WALLcontrol™ Reinforced Aluminum Flashing

### Siplast's Commitment to Sustainability

Siplast has many products—commercial wall systems, and roofing, waterproofing, and vegetated roofing systems—that contribute to LEED categories including Sustainable Sites, Water Efficiency, Energy & Atmosphere, Materials & Resources, Indoor Environmental Quality, and Innovation In Operation & Regional Priority. For more information, visit Siplast's Sustainability Solutions page:

<https://www.siplast.com/solutions/sustainability-solutions>

### Helping Our Partners Meet Their Environmental Goals

From air and water-resistant barriers to bright white liquid-applied roof membranes and a granule surfacing that can help neutralize harmful nitrogen oxides found in the atmosphere, Siplast has been designing products our partners can use to meet their environmental and sustainability goals. Siplast has systems that meet environmental standards, like California Title 24 Part 6, and can help contribute toward sustainability credits in programs like the U.S. Green Building Council Leed v4 program. For us, this is an ongoing commitment.

Siplast has developed a series of Manufacturer Inventories for our WALLcontrol™ product line to support our partners' demands for transparency and meet requirements of certain environmental standards and certification programs. The self-adhesive **Siplast WALLcontrol™ Reinforced Aluminum Butyl Adhered Air and Water-Resistive Barrier** features a high-temperature stable and low-temperature application butyl adhesive with a split siliconized release liner. This primerless, non-vapor permeable AWB serves as both an air barrier membrane and a water-resistive barrier membrane for commercial wall systems. WALLcontrol™ Reinforced Aluminum AWB is also flexible and UV resistant.

The self-adhesive **Siplast WALLcontrol™ Reinforced Aluminum Butyl Adhered Flashing** features a high-temperature stable and low-temperature application butyl adhesive with a siliconized release liner. This multi-purpose, self-adhered flashing accessory is highly compatible with many substrates for commercial wall systems. It's flexible, hand-formable, and UV resistant. WALLcontrol Reinforced Aluminum Flashing offers primerless application which is ideal in a variety of transitions and penetrations.

## Product Ingredient Reporting

This manufacturer inventory report is intended to summarize the chemical attributes of this product. This report meets the requirements of the LEED v4 and v4.1 MR Credit: Building Product Disclosure and Optimization Ingredients - Option 1.

The following table lists ingredients and their CAS numbers (if applicable) for ingredients that are equal to or greater than 0.1% (1,000 ppm) of the product. The ingredient name and Chemical Abstract Service Registration Number is listed for publicly available ingredients. CAS numbers for ingredients defined as proprietary (i.e., trade secret) have been withheld; however, the ingredient amount and hazard are disclosed when appropriate.

Ingredient	Ingredient Role	Ingredient Amount	CAS No.	Hazard Category
Synthetic Butyl Compounds	Adhesive	70-90 %	Proprietary	Non-hazardous
Polypropylene	Structural component	5-15 %	9003-07-0	LT-1
Polyethylene	Structural component	0.1-5%	9002-88-4	LT-UNK
Aluminum	Water resistant surfacing	0.1-10 %	7429-90-5	BM-1

## Siplast, Inc

14911 Quorum Drive, Suite 600  
Dallas, TX 75254  
800-922-8800

Disclaimer: Information provided herein is for illustrative and general information purposes only, and is not intended to provide specific advice, and should not be relied upon in that regard.

User is responsible for determining whether the Siplast products and information in this document are appropriate for their intended use of the products and that such use and materials are in compliance with applicable codes, laws and other government regulations. Prior to each use of any Siplast products, user must always read and follow the warnings and instructions on the product's current product label, Product Data Sheet, and Safety Data Sheets.

NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES OR GUARANTEES SPECIFICALLY PROVIDED BY SIPLAST FOR A PARTICULAR PROJECT. ALL IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY DISCLAIMED. Siplast assumes no obligation or liability for the information contained in this document.