

**Note: This detail applies to PVC and PVC KEE systems only** —

**Note: This detail applies to PVC and PVC KEE systems only**

SEALANT

CONDUCTOR HEAD

PARASOLO WATER-BLOCK SEALANT

PARASOLO FLEECE-BACK MEMBRANE (up to 54 inches requires approved low rise foam adhesive)

PARADIENE 20 FLASHING REINFORCING (fully adhere, see note #1)

CONTINUOUS HEAT-WELDED LAP 2" MIN.

PARASOLO KEE MEMBRANE TARGET (see note #2)

PARAPRO 123 FLASHING SYSTEM or PARAFLEX 531 LIQUID FLASHING (fully adhere, see note #3)

PARASOLO WATER-BLOCK SEALANT

PARAFAST FASTENERS 12" O.C.

METAL SCUPPER SLEEVE (set in Parasolo Water-Block Sealant & fasten - abrade flange to receive Parapro or Paraflex)

PARAPRO 123 FLASHING SYSTEM or PARAFLEX 531 LIQUID FLASHING (fully adhere, see note #3)

PARASOLO KEE MEMBRANE TARGET (set lap at metal scupper flange in Parasolo Water-Block Sealant, see note #2)

CONTINUOUS HEAT-WELDED LAP 2" MIN.

PARASOLO FLEECE-BACK MEMBRANE (adhere)

PARADIENE 20 (fully adhere)

APPROVED COVERBOARD

ROOF INSULATION

ROOF DECK

2" MIN.

4"

3"

3"

NOTES

1. PARADIENE 20 FLASHING REINFORCING IS REQUIRED FOR EXPOSED PARADIENE IN LONG-TERM PHASE-CONSTRUCTION OR FOR SPECIAL GUARANTEE REQUIREMENTS. THE PARADIENE 20 IS OPTIONAL IN STANDARD NON-PHASE CONSTRUCTION APPLICATIONS.
2. PARASOLO KEE MEMBRANE IS REQUIRED AT LOCATIONS TO RECEIVE PARAPRO OR PARAFLEX 531 LIQUID FLASHING SYSTEMS. PARAFLEX 531 LIQUID FLASHING CAN BE UTILIZED WITH PARASOLO PVC KEE ONLY.
3. REFER TO SIPLAST PREPARATION GUIDELINES FOR PROPER SURFACE TREATMENT OF ALL MATERIALS PRIOR TO APPLICATION OF PARAPRO OR PARAFLEX 531 LIQUID FLASHING MATERIALS.
4. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.
5. PARAFLEX 531 LIQUID FLASHING CAN BE UTILIZED WITH PARASOLO PVC KEE ONLY.

**Rev:** 06.06.2023