

PARASOLO ROOF MEMBRANE - INSULCEL LIGHTWEIGHT INSULATING CONCRETE

COUNTER FLASHING

WOOD CURB

8" MIN.

- PARASOLO FLEXSEAL CAULK
GRADE SEALANT

- PARASOLO MEMBRANE TARGET
(see note #2)

– PARAFAST FASTENERS/PLATES
(12 inches o.c.)

– HEAT WELDED LAP (see note #1)

- PARASOLO FLEECE-BACK MEMBRANE (adhere to horizontal surfaces as shown)

– INSULCEL LIGHTWEIGHT INSULATING CONCRETE SYSTEM

– PREPARED SUBSTRATE
(follow Siplast specifications)

LEGEND

HEAT WELD

SEALANT

1. FOR HEAT-WELDING LAPS USE 1" MINIMUM WELD TO 1-1/2" MAXIMUM WELD.
2. PARASOLO PVC KEE MEMBRANE IS REQUIRED AT LOCATIONS TO RECEIVE PARAFLEX 531 LIQUID FLASHING SYSTEMS.
3. REFER TO SIPLAST PREPARATION GUIDELINES FOR PROPER SURFACE TREATMENT OF ALL MATERIALS PRIOR TO APPLICATION OF PARAPRO OR PARAFLEX 531 LIQUID FLASHING MATERIALS.
4. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.

REF: CURB - PARASOLO - INSULATED - LIQUID FLASHING

Rev: 06.08.2023



www.siplast.com