

PARASOLO FLEECE BACK MEMBRANE - INSULCEL LIGHTWEIGHT INSULATING CONCRETE

ADHESIVE

PARASOIL FLEXSEAL CAULK GRADE SEALANT

PARASOIL WATER-BLOCK SEALANT

STAINLESS STEEL CLAMP

PARASOIL BONDING ADHESIVE

PARASOIL SMOOTH MEMBRANE & TARGET (extend target 1/2 inch up the pipe, see note #1)

PARAFAST FASTENERS/PLATES (four fasteners & plates around penetration)

HEAT WELDED LAP (see note #1)

PARASOIL FLEECE-BACK MEMBRANE (adhere to horizontal surfaces as shown)

INSULCEL LIGHTWEIGHT INSULATING CONCRETE SYSTEM

8" MIN.

1"

1/4"

PARASOIL FLEXSEAL CAULK GRADE SEALANT

PREPARED SUBSTRATE (follow Siplast specifications)

NOTES

1. FOR HEAT-WELDED LAP USE 1" MINIMUM TO 1-1/2" MAXIMUM WELD.
2. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.

Rev: 06.15.2023