

PARASOLO FLEECE BACK MEMBRANE INSULCEL LIGHTWEIGHT INSULATING CONCRETE

SEALANT

COUNTER FLASHING
(compression fit)

SEE TERMINATION DETAIL

PARASOLO SMOOTH
REINFORCED MEMBRANE
(adhered with Parasoil Bonding
Adhesive or Parasoil Quick Spray
Adhesive, see note #3)

PARASOLO WATER-BLOCK SEALANT

PARAFAST FLAT TERMINATION
BAR (fastened 8 inches o.c.)

HEAT WELDED LAP (see note #1)

PARASOLO FLEECE-BACK MEMBRANE
(adhere to vertical and horizontal surfaces as shown)

INSULCEL LIGHTWEIGHT
INSULATING CONCRETE SYSTEM

3"

3"

8" MIN.

PREPARED SUBSTRATE
(follow Siplast specifications)

PARASOLO FLEXSEAL
CAULK GRADE SEALANT

PARASOLO WATER-
BLOCK SEALANT

PARAFAST LIP
TERMINATION BAR
(fastened 8 inches o.c.)

PARASOLO
REINFORCED
MEMBRANE

TERMINATION DETAIL

NOTES:
1. FOR HEAT WELDING LAPS USE 1/4" MINIMUM WELD TO 1/2" MAXIMUM WELD

1. FOR HEAT-WELDING LAPS USE 1" MINIMUM WELD TO 1-1/2" MAXIMUM WELD.
2. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.
3. PARASOLO BONDING ADHESIVE CAN BE USED UP TO A MAXIMUM FLASHING HEIGHT OF 54 INCHES. ADDITIONAL TERMINATION IS REQUIRED FOR FLASHING HEIGHTS ABOVE 54 INCHES WHEN PARASOLO BONDING ADHESIVE IS USED. CONTACT THE SIPLAST TECHNICAL DEPARTMENT FOR ADDITIONAL INFORMATION.

Rev: 06.15.2023