

PARASOLO FLEECE BACK MEMBRANE INSULCEL
LIGHTWEIGHT INSULATING CONCRETE

HEAT WELD

8" MIN.

WALL (prepare masonry surfaces to receive the Parapro 123 Flashing System)

PARAPRO 123 FLASHING SYSTEM or PARAFLEX 531 LIQUID FLASHING (fully adhere)

PARASOLO FLEXSEAL CAULK GRADE SEALANT

PARASOLO MEMBRANE TARGET (see note #1)

PARAFAST FASTENERS/PLATES (12 inches o.c.)

HEAT WELDED LAP (see note #2)

PARASOLO FLEECE-BACK MEMBRANE (adhere to horizontal surfaces as shown)

INSULCEL LIGHTWEIGHT INSULATING CONCRETE SYSTEM

1" MIN.

PREPARED SUBSTRATE (follow Siplast specifications)

1. PARASOLO KEE MEMBRANE IS REQUIRED AT LOCATIONS TO RECEIVE PARAFLEX 531 LIQUID FLASHING SYSTEMS.
2. FOR HEAT-WELDING LAPS USE 1" MINIMUM WELD TO 1-1/2" MAXIMUM WELD.
3. REFER TO SIPLAST PREPARATION GUIDELINES FOR PROPER SURFACE TREATMENT OF ALL MATERIALS PRIOR TO APPLICATION OF PARAPRO OR PARAFLEX 531 LIQUID FLASHING MATERIALS.
4. REQUIREMENTS AND RECOMMENDATIONS DETAILED IN CURRENT SIPLAST SPECIFICATIONS SHALL APPLY IN ADDITION TO THE ABOVE DRAWING.

www.siplast.com